


# Защита от перегиба для серии SF



Наименование	Серия	Защита от перегиба		Внешний диаметр кабеля		Материал	Температурный диапазон
		A	L	мин.	макс.		
SF6-FZ(2-2.5)-TBK	SF6	2.3	26	2	2.5	ТПУ	-40°C ~ 80°C
SF6-FZ(2.6-3)-TBK		2.8	26	2.6	2.8		
SF6-FZ(3-3.5)-TBK		3.3	26	3	3.5		
SF6-FZ(3.6-4)-TBK		3.8	26	3.6	4		
SF8-FZ(3-3.5)-TBK	SF8	3.3	28	3	3.5		
SF8-FZ(3.6-4)-TBK		3.8	28	3.6	4		
SF8-FZ(4-4.5)-TBK		4.3	28	4	4.5		
SF8-FZ(4.6-5)-TBK		4.8	28	4.6	5		
SF10-FZ(3-3.5)-TBK	SF10	3.3	35	3	3.5		
SF10-FZ(3.6-4)-TBK		3.8	35	3.6	4		
SF10-FZ(4-4.5)-TBK		4.3	35	4	4.5		
SF10-FZ(4.6-5)-TBK		4.8	35	4.6	5		
SF10-FZ(5-5.5)-TBK		5.3	35	5	5.5		
SF10-FZ(5.6-6)-TBK		5.8	35	5.6	6		
SF10-FZ(6-6.5)-TBK	6.3	35	6	6.5			
SF12-FZ(5-5.5)-TBK	SF12	5.3	42	5	5.5		
SF12-FZ(5.6-6)-TBK		5.8	42	5.6	6		
SF12-FZ(6-6.5)-TBK		6.3	42	6	6.5		
SF12-FZ(6.6-7)-TBK		6.8	42	6.6	7		
SF12-FZ(7-7.5)-TBK		7.3	42	7	7.5		
SF12-FZ(7.6-8)-TBK		7.8	42	7.6	8		
SF16-FZ(8-8.5)-TBK	SF16 SF20	8.3	56	8	8.5		
SF16-FZ(8.6-9)-TBK		8.8	56	8.6	9		
SF16-FZ(9-9.5)-TBK		9.3	56	9	9.5		
SF16-FZ(9.6-10)-TBK		9.8	56	9.6	10		
SF16-FZ(10-10.5)-TBK		10.3	56	10	10.5		
SF16-FZ(10.6-11)-TBK		10.8	56	10.6	11		
SF16-FZ(11-11.5)-TBK		11.3	56	11	11.5		
SF16-FZ(11.6-12)-TBK		11.8	56	11.6	12		